



N-Channel 60-V (D-S) MOSFETs

PRODUCT SUMMARY				
Part Number	$V_{(BR)DSS}$ Min (V)	$r_{DS(on)}$ Max (Ω)	$V_{GS(th)}$ (V)	I_D Min (A)
VN10LLS	60	5 @ $V_{GS} = 10$ V	0.8 to 2.5	0.32
VN0605T		5 @ $V_{GS} = 10$ V	0.8 to 3.0	0.18
VN0610LL		5 @ $V_{GS} = 10$ V	0.8 to 2.5	0.28
VN2222LL		5 @ $V_{GS} = 10$ V	0.6 to 2.5	0.23

FEATURES


- Low On-Resistance: 2.5 Ω
- Low Threshold: <2.1 V
- Low Input Capacitance: 22 pF
- Fast Switching Speed: 7 ns
- Low Input and Output Leakage

BENEFITS

- Low Offset Voltage
- Low-Voltage Operation
- Easily Driven Without Buffering
- High-Speed Circuits
- Low Error Voltage

APPLICATIONS

- Direct Logic-Level Interface: TTL/CMOS
- Solid State Relays
- Drivers: Relays, Solenoids, Lamps, Hammers, Displays, Memories, Transistors, etc.
- Battery Operated Systems




Top View
VN0610LL
VN2222LL

Front View




"S" = Siliconix Logo
xxyy = Date Code

TO-92S




Top View
VN10LLS

Front View




"S" = Siliconix Logo
xxyy = Date Code

TO-236 (SOT-23)



Top View
VN0605T

VN0605T



V2 = Part Number Code for VN0605T
w = Week Code
// = Lot Traceability

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)							
Parameter	Symbol	VN10LLS	VN0605T	VN0610LL	VN2222LL	Unit	
Drain-Source Voltage	V_{DS}	60	60	60	60	V	
Gate-Source Voltage—Non-Repetitive ^b	V_{GSM}	± 30	± 30	± 30	± 30		
Gate-Source Voltage—Continuous	V_{GS}	± 20	± 20	± 20	± 20		
Continuous Drain Current ($T_J = 150^\circ\text{C}$)	I_D	$T_A = 25^\circ\text{C}$	0.32	0.18	0.28	0.23	A
		$T_A = 100^\circ\text{C}$	0.2	0.11	0.17	0.14	
Pulsed Drain Current ^a	I_{DM}	1.4	0.72	1.3	1.0		
Power Dissipation	P_D	$T_A = 25^\circ\text{C}$	0.9	0.36	0.8	0.8	W
		$T_A = 100^\circ\text{C}$	0.4	0.14	0.32	0.32	
Thermal Resistance, Junction-to-Ambient	R_{thJA}	139	350	156	156	$^\circ\text{C/W}$	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 150				$^\circ\text{C}$	

Notes

- Pulse width limited by maximum junction temperature.
- $t_p \leq 50 \mu\text{s}$.



SPECIFICATIONS (T _A = 25 °C UNLESS OTHERWISE NOTED)										
Parameter	Symbol	Test Conditions	Typ ^a	Limits						Unit
				VN10LLS VN0610LL		VN0605T		VN2222LL		
				Min	Max	Min	Max	Min	Max	
Static										
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = 100 μA	70	60				60		V
		V _{GS} = 0 V, I _D = 10 μA	70			60				
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 1 mA	2.1	0.8	2.5	0.8	3.0	0.6	2.5	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V					±100		±100	nA
		T _J = 125 °C					±500			
Zero Gate-Voltage Drain Current	I _{DSS}	V _{DS} = 0 V, V _{GS} = ±30 V			±100					μA
		V _{DS} = 50 V, V _{GS} = 0 V			10		1.0			
		T _J = 125 °C			500		500			
		V _{DS} = 48 V, V _{GS} = 0 V							10	
		T _J = 125 °C							500	
On-State Drain Current ^b	I _{D(on)}	V _{DS} = 10 V, V _{GS} = 10 V	1000	750		500		750		mA
Drain-Source On-Resistance ^b	r _{DS(on)}	V _{GS} = 4.5 V, I _D = 50 mA	4.5				7.5			Ω
		V _{GS} = 5 V, I _D = 0.2 A	4.5		7.5				7.5	
		V _{GS} = 10 V, I _D = 0.5 A	2.4		5		5		7.5	
		T _J = 125 °C	4.4		9		10		13.5	
Forward Transconductance ^b	g _{fs}	V _{DS} = 10 V, I _D = 0.5 A	230	100				100		mS
		V _{DS} = 10 V, I _D = 0.2 A	180			80				
Common Source Output Conductance ^b	g _{os}	V _{DS} = 5 V, I _D = 50 mA	500							μS
Dynamic										
Input Capacitance	C _{iss}	V _{DS} = 25 V, V _{GS} = 0 V f = 1 MHz	22		60		60		60	pF
Output Capacitance	C _{oss}		11		25		25		25	
Reverse Transfer Capacitance	C _{rss}		2		5		5		5	
Switching^c										
Turn-On Time	t _{ON}	V _{DD} = 15 V, R _L = 23 Ω, I _D ≅ 0.6 A V _{GEN} = 10 V, R _G = 25 Ω	7		10				10	ns
Turn-Off Time	t _{OFF}		7		10				10	
Turn-On Time	t _{ON}	V _{DD} = 30 V, R _L = 150 Ω, I _D ≅ 0.2 A V _{GEN} = 10 V, R _G = 25 Ω	7				20			
Turn-Off Time	t _{OFF}		11				20			







Notes

- a. Typical values are for DESIGN AID ONLY, not guaranteed nor subject to production testing.
- b. Pulse test: PW ≤ 300 μs duty cycle ≤ 3%.
- c. Switching time is essentially independent of operating temperature.





VNBF06



TYPICAL CHARACTERISTICS (T_A = 25°C UNLESS OTHERWISE NOTED)



TYPICAL CHARACTERISTICS (T_A = 25°C UNLESS OTHERWISE NOTED)





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.