


Part Number: SL15 22102

Ordering Different Lead Types:

Inside Kinked Leads	Use -A after Ametherm's part #
Outside Kinked Leads	Use -B after Ametherm's part #

For example: to order an inside kinked lead use part number SL15 22102-A



Electrical Specifications:

Resistance @ 25°C	220.0 Ω \pm 25%
Max Steady State Current Up to 65°C	2.0 A
Max Recommended Energy Rating (Joules)	50.0 J
Actual Failure Point of Instantaneous Energy (Joules)	130.0 J
Resistance @ 100% of Max Current	0.900 Ω
Resistance @ 50% of Max Current	1.900 Ω
Body Temperature @ 100% Current Rating	191 °C
Dissipation Constant	18mW/°C
Thermal Time Constant	45 seconds
Material Type	"L"
Max Recommended Capacitance @ 120/240 VAC	3200 μ F/800 μ F

Mechanical Specifications:

D	15.0 \pm 0.5 mm
T	5.0 \pm 0.5 mm
Lead Diameter	0.8 \pm 0.1 mm
S	7.8 \pm 2.0 mm
L	38.0 \pm 9.0 mm
Straight Leads	5.0 \pm 1.0 mm
Coating Run Down	
B	7.50 \pm 0.70 mm
C	2.82 \pm 0.5 mm
Coating Run Down on the Straight Leads	5.00 \pm 0.5 mm