

Part Number: SL15 7R004

Ordering Different Lead Types:

Inside Kinked Leads	Use -A after Ametherm's part #
Outside Kinked Leads	Use -B after Ametherm's part #

For example: to order an inside kinked lead use part number SL15 7R004-A



Electrical Specifications:

Resistance @ 25°C	10.0 Ω \pm 20%
Max Steady State Current Up to 65°C	4.0 A
Max Recommended Energy Rating (Joules)	55.0 J
Actual Failure Point of Instantaneous Energy (Joules)	120.0 J
Resistance @ 100% of Max Current	0.098 Ω
Resistance @ 50% of Max Current	0.210 Ω
Body Temperature @ 100% Current Rating	157 °C
Dissipation Constant	18.0Mw/°C
Thermal Time Constant	54 seconds
Material Type	"C"
Max Recommended Capacitance @ 120VAC/265VAC	3800 μ F/780 μ F

Mechanical Specifications:

D	15.0 \pm 0.5 mm
T	5.0 \pm 0.3 mm
Lead Diameter	0.8 \pm 0.1 mm
S	7.80 \pm 0.6 mm
L	38.0 \pm 3.0 mm
B	7.50 \pm 0.70 mm
C	2.82 \pm 0.5 mm
Coating Run Down on the Straight Leads	5.00 \pm 0.5 mm