




TYPE	Photo	Series	Type	Rating (max.)	Operating force	Operating life	DIP P/N
						(Without load)	
DETECTOR		<a href="#">SPPB</a>	General-purpose type	0.1A 30V DC	0.35N max.	50,000 cycles	NA
		<a href="#">SPVE</a>	Compact one-way operation type	0.1A 30V DC	0.3N max.	50,000 cycles	NA
		<a href="#">SPPW8</a>	One-way operation type	0.1A 30V DC	0.3N max.	100,000 cycles	NA
		<a href="#">SPVM</a>	Compact two-way operation type	1mA 5V DC	0.4N max.	50,000 cycles	BTE
		<a href="#">SPVR</a>	Low-profile lever type	1mA 5V DC	0.35N max.	50,000 cycles	TU
		<a href="#">SSCU</a>	Compact micro switch type	0.1A 12V DC	0.5N max.	10,000 cycles	NA
		<a href="#">SSCT</a>	Micro switch type	0.1A 12V DC	0.7±0.3N	10,000 cycles	NA
		<a href="#">SSCF</a>	Two-way detection type	0.1A 12V DC	0.7N max.	50,000 cycles	NA
		<a href="#">SSCM</a>	Compact two-way detection type	1mA 5V DC	0.35N max.	50,000 cycles	DTE
		<a href="#">SPVP</a>	Low-profile one-way operation type	1mA 5V DC	0.55N max.	50,000 cycles	FTE
		<a href="#">SPVN</a>	Low-profile two-way operation type	1mA 5V DC	0.35N max.	50,000 cycles	NA
		<a href="#">SPVS</a>	Compact two-way operation type	1mA 5V DC	0.35N max.	50,000 cycles	ELH
		<a href="#">SPVT</a>	Two-way operation type	50mA 20V DC	0.4N max.	100,000 cycles	NA
		<a href="#">SPVL</a>	Low-profile tri-way operation type	1mA 5V DC	0.35N max.	50,000 cycles	NA

	<a href="#">SSCW</a>	Two-way detection type with female connector terminal	0.1A 12V DC	1N max.	100,000 cycles	NA
	<a href="#">SPVQ5</a>	Micro switch type with female connector terminal	0.1A 12V DC	2N max.	300,000 cycles	NA
	<a href="#">SPVQ1</a>	Water-proof long travel type	0.1A 12V DC	Push: 2N max. Actuator: 5.9N max.	300,000 cycles	NA
	<a href="#">SPVQ3</a>	Water-proof type	Standard: 0.1A 12V DC Long life: 0.3A 16V DC	Push: 1±0.5N Actuator: 3N max.	Standard: 300,000 cycles Long life: 1,200,000 cycles	NA
	<b>NEW</b> <a href="#">SPVQ4H</a>	Water-proof type	0.1A 12V DC	0.3N max.	300,000 cycles	NA
	<a href="#">SPVQ6</a>	Compact water-proof type	0.1A 12V DC	Push: 1±0.5N Actuator: 3N max.	300,000 cycles	NA
	<a href="#">SPVQ7</a>	Water-proof type	0.1A 12V DC	1±0.5N	300,000 cycles	NA
	<b>NEW</b> <a href="#">SPVQ8</a>	Compact water-proof type	0.1A 12V DC	1±0.5N	Standard: 300,000 cycles Long life: 1,000,000 cycles	NA
	<b>NEW</b> <a href="#">SPVQ9</a>	Water-proof type (Sliding contact type)	50mA 26V DC	1±0.5N	300,000 cycles	NA
	<a href="#">SPVQA</a>	Water-proof type (Fork terminals)	0.1A 12V DC	1±0.5N	300,000 cycles	NA
	<a href="#">SSCN</a>	Water-proof lever type	0.1A 12V DC	2N max.	100,000 cycles	NA
	<a href="#">SPPY5</a>	For telephone-hook	50mA 48V DC	0.8N max.	300,000 cycles	NA